



RS232C-ISOLATOR

MODEL: LD14I



INTRODUCTION

Milestone RS232 Isolator Model LD-14I is designed for protection of expensive system interface by providing optical isolation between the two communicating devices. Application for these converters can be for factory automation, programmable logic controllers, attendance recording systems, Barcode Readers, remote data transmission, remote terminals, EPABX etc.

SPECIFICATIONS

Signals	RS232 - TxD, RxD, DTR, DSR & SIGNAL GND at input (D25 / 9 Female Connector) and output (D9 / 25 Male Connector)
Max. Distance	15 meters.
Transient Protection	2500 V Peak
Optical Isolation	2500 V Peak between input and output port circuit
LED Indication	TD, RD, POWER, TC(DTR), RC(DSR).
Power Supply	Mains Input-230V, 50 Hz
Power	Max. 20 VA Built-In Power Supply.
Size	135mm x 145mm x 57mm



TABLE I: Input RS 232 Port – D25 Female Connector

D9-F Pin No.	D25-F Pin No.	Signal	Input/Out
3	2	Rx	Input
2	3	Tx	Output
5	7	Signal Ground	-
6	6	DTR	Output
4	20	DSR	Input
7, 8, 1	4, 5, 8	RTS, CTS, CD	-

TABLE II: Output RS 232 Port – D25 Male Connector

D9-M Pin No.	D25-M Pin No.	Signal	Input/Out
3	2	Tx	Output
2	3	Rx	Input
5	7	Signal Ground	-
6	6	DSR	Input
4	20	DTR	Output
7, 8, 1	4, 5, 8	RTS, CTS, CD	-