

6 in 4x1 Quad View Switcher

MP-SC6T-MV QUAD VIEW Switcher



The presentation switcher offers four HDMI, one display port and one USB-C inputs along with mirrored HDMI and HDBaseT outputs. The HDBaseT output supports PoC and can be paired with a compatible HDBaseT receiver to extend 4k@30Hz/1080P signal up to 40 meters (131ft)/70 meters (230ft) all over a single CATx cable.

Applications:

This unit can cater to any Boardroom, conference room, training room or Home theatre, Medical and Operation Room setup for up to Quad Video display simultaneously.

Compatibility:

Support **HDMI1.4**, and the max resolution supports 4Kx2K@30Hz 4:4:4, HDR, **HDCP2.0** compliant, External audio embedded support for HDMI input. HDCP compliant, EDID management,, **Support CEC control**, source or display device via IR Remote and RS232 commands, LED indicators show the switching status, Support Hot-plug, **auto Switching**, Convenient online firmware update. **GUI control**.



Milestone PRO

Features:

- 4K Presentation Switcher with HDBaseT output.
- Supports seamless and auto switching.
- HDMI 1.4 and HDCP 2.2 compliant.
- Extends HDMI signals to distance up to 40 meters at 4K and 70 meters at 1080p.
- Supports audio embedded, audio de-embedding and microphone audio mixing.
- Supports multi-view and up to 16 modes can be selected.
- Controllable via front panel buttons, GUI, IR remote, RS232 and CEC.

Inputs:

- 4 x HDMI, 1 DP, 1 C-USB
- 1 x IR (3.5mm mini jack) for Control by Remote
- 1 x RS232 for Control through third party device

Output:

- 1 HDMI (Female type A)
- 1 HDBT RJ-45
- 1 Audio (3.5mm mini stereo audio jack)

Power:

- 100-230V > 24V DC.

Size:

- (H/W/D) = 44mm X 250mm X 200mm

Packing:

- 1* MP-SC6T-MV
- 2* Mounting ears
- 4* Mounting Screws
- 1* RS232 Cable
- 4* Plastic cushions
- 1* IR Receiver
- 1* Power adaptor
- 1* IR Remote Controller
- 1* User manual



Connectivity Diagram:

