

# IP TO RS232\_485\_422

## IP-2535U

Milestone IP-2335U is an Ethernet to RS232, RS422 OR RS485 convertor.

It is designed for high speed isolated data transmission between computer system through it's Ethernet port to other peripherals or devices having RS232/RS422/RS485 interface.

### Applications

- Factory Automation
- Programmable logic Controllers
- Attendance Recording Systems
- Barcode Readers
- Remote Data Transmission
- Remote Terminal
- EPABX and many more application...



IP-2535U



### Specifications:

- Input: E-net [RJ-45 Connector]
- Output: Standard 7 pin Phoenix connector
- Output Protection: Spike suppression and Opto-Isolation for each signal
- Data format supported: Data bit-8, Stopbit-1, Parity: Odd, Even or No Parity
- Baud rate: 300bps to 19.2Kbps
- Hand Shaking : X-ON/X-OFF
- Selection (Output): 2 way slide s/w, for 4 / 2 wire
- Selection for 2 wire half duplex or 4 wire full duplex application
- Output cable: Should be shielded twisted pair cable
- Front panel LED for (Power, TD & RD) signal

### Power:

Power Adapter supplied 230V A.C. to 5V -0.6Amp.

### Size:

87mm / 22mm / 73mm (W/D/H) >

### Packing:

1\*IP-2535u unit, 1\*Driver CD, 1Mtr\* cat-5 cable, 1\*Adapters for power. & Shipping Weight : 600g

### Product Weight:

Shipping Weight : 440 grams  
Product weight : 222 grams