



VGA SWITCHER

Milestone's "VGA Switcher" is a unit whereby multiple (2/4/8/16) VGA inputs (Optional* VGA+Audio) can be switched to two or multiple (simultaneous) VGA outputs. The switchers are user configurable for manual or auto switching (scanning) modes. This auto switching can be enabled or disabled via a rear panel slide switch. Auto switching allows any input of the switcher to be selected automatically when the switcher detects a sync signal (Sync signal detection).

FEATURES:

- Simultaneous two output for Selected input
- Compatible to multisync VGA, SVGA, SXGA, XGA
- Video Bandwidth - 300 MHz
- Individual local keypad on front panel
- Individual RF Remote keypad *
- Remote contact closure on back panel
- RS232C interface
- RS422/RS485 interface *
- Active PCs selected or scanned in auto scan mode (Sync signal detection)
- Gain controlled output for optimal viewing
- LED indication for working set
- Each display can drive up to 100/150 meters (with good quality cable)
- Input & output connectors for VGA : 15pin D type Female
- RS232 Port 9 : Pin female
- Contact closure Port : 9 Pin male
- Audio port : Captive Screw in VGA Audio Switcher



* Optional

MODELS AVAILABLE:

Model	Inputs	Outputs	Size in mm	Weight
ML 201 VGA	2	1	115 x 45 x 28	0.2 Kg
ML 202 VGA	2	2	288 x 130 x 52	1.4 Kg
ML 402 VGA#	4	2	288 X 130 X52	1.9 Kg
ML 802 VGA#	8	2	288 X 130 X68	2.3 Kg
ML 1602 VGA*	16	2	19" - 2U	4.72 Kg
ML 203 VGA	2	2	288 x 130 x 52	1.5 Kg

VGA + Audio Switcher*
Rack Mount 19" - 2U unit*

APPLICATIONS:

- Presentation & Conference room
- Production Studios
- Rental & staging activity
- Multiple input multiple display

* Optional

Models available in 19" - Rack

